



(19)

(11) Publication number: **62166**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **61009511**(51) Intl. Cl.: **G06F 7/52**(22) Application date: **20.01.86**

<p>(30) Priority:</p> <p>(43) Date of application publication: <b>22.07.87</b></p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: <b>FUJITSU LTD</b></p> <p>(72) Inventor: <b>TOYAMA KEI</b></p> <p>(74) Representative:</p>
---	---

**(54) WALLACE TREE CIRCUIT**

(57) Abstract:

**PURPOSE:** To allow a Wallace tree circuit to operate fast by using a signal which has passed through less gates between the carry signal and sum signal of a full adder as the input to the full-adder of the next stage.

**CONSTITUTION:** In the Wallace tree circuit, the sum output S of the full-adder FA of the 2nd stage is inputted to the FA of the 3rd stage and the output S of the 3rd stage is inputted to the FA of the 4th stage. The outputs S of two FAs of the 1st stage are inputted to the FAs of the 3rd stage and the 4th stage. Namely, the FA of the 2nd stage input a direction input signal and the carry output C of the FA of the 1st stage as the previous digit. When FAs are composed of three-input NOR gate circuits, outputs C are two gates and outputs S are three gates, so the number of gates from the input of the FA of the 1st stage to the outputs S and C of the 4th stage is one less than that of a conventional example, so

fast addition is enabled.

COPYRIGHT: (C)1987,JPO&Japio

